Please type a plus sign (+1	inside this box	→	+
lease type a plus sign (. ' /	HISIDE HIS DOX	-	

PTO/SB/05 (4/98)
Approved for use through 09/30/2000 OMB 0651-0032
Patent and Trademark Office. U.S. DEPARTMENT OF COMMERCE

Lunder the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

UTILITY PATENT APPLICATION TRANSMITTAL

Attorney Docket No. 500.37136CX1

First Inventor or Application Identifier Yutaka NAGAI et al

Title | See 1 in Addendum

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b)) Express Mail Label No.

(in	
APPLICATION ELEMENTS See MPEP chapter 600 concerning utility patent application contents.	Assistant Commissioner for Patents ADDRESS TO: Box Patent Application Washington, DC, 20231
X * Fee Transmittal Form (e.g., PTO/SB/17) (Submit an original and a duplicate for fee processing) X Specification	Microfiche Computer Program (Appendix) Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary) a. Computer Readable Copy b. Paper Copy (identical to computer copy) c. Statement verifying identity of above copies ACCOMPANYING APPLICATION PARTS 7. Assignment Papers (cover sheet & document(s)) 8. 37 C.F.R.§3 73(b) Statement Power of (when there is an assignee) Attorney 9. English Translation Document (if applicable) 10. X Information Disclosure Statement (IDS)/PTO-1449 Citations 11. Preliminary Amendment 12. X Return Receipt Postcard (MPEP 503) (Should be specifically itemized) * Small Entity Statement filed in prior application Status still proper and desired (PTO/SB/09-12) 14. (if foreign priority is claimed) Other.
	nying continuation or divisional application and is hereby incorporated by has been inadvertently omitted from the submitted application parts.
17. CORRESPOND	
X Customer Number or Bar Code Labe i (Insert Customer No. or Att	or Correspondence address below
Name	
Address	
City State	Zip Code
Country Telephone	Fax
Name (Print/Type) Melvin Kraus	Registration No. (Attorney/Agent) 22,466

Burden Hour Statement This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office Washington, DC 20231 DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO. Assistant Commissioner for Patents, Box Patent, Application, Washington, DC 20231



Attachment to PTO/SB/05 (4/98) Utility Patent Application Transmittal

1. REPRODUCTION APPARATUS AND REPRODUCTION METHOD OF DIGITAL VIDEO SIGNAL OR AUDIO SIGNAL

09/712970

PTO/SB/17 (12/99)
Approved for use through 09/30/2000 OMB 0651-0032
Patent and Trademark Office U.S. DEPARTMENT OF COMMERCE

Patent and Trademark Office US DEPARTMENT OF COMMERCE Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

FEE TRANSMITTAL Complete if Known Application Number for FY 2000 November 16, 2000 Filing Date Yutaka NAGAI et al Patent fees are subject to annual revision First Named Inventor Small Entity payments must be supported by a small entity statement, **Examiner Name** otherwise large entity fees must be paid See Forms PTO/SB/09-12 See 37 C F R §§ 1 27 and 1 28 Group / Art Unit TOTAL AMOUNT OF PAYMENT (\$)950.00 500.37136CX1 Attorney Docket No.

METHOD OF PAYMENT (check one)	METHOD OF PAYMENT (check one) FEE CALCULATION (continued)				
The Commissioner is hereby authorized to charge indicated fees and credit any overpayments to Deposit	3. ADDITIONAL FEES Large Entity Small Entity Fee Fee Fee Fee Code (\$) Code (\$)	Fee Paid			
Account Number 01-2135	Code (\$) Code (\$) 105 130 205 65 Surcharge - late filing fee or oath	0.00			
Deposit Account	127 50 227 25 Surcharge - late provisional filing fee or cover sheet	0.00			
Name L	139 130 139 130 Non-English specification	0.00			
Charge Any Additional Fee Required Under 37 CFR §§ 1 16 and 1 17	147 2,520 147 2,520 For filing a request for reexamination	0.00			
2. X Payment Enclosed:	112 920* 112 920* Requesting publication of SIR prior to Examiner action	0.00			
Check Money Order Tother	113 1,840* 113 1,840* Requesting publication of SIR after Examiner action	0.00			
FEE CALCULATION	115 110 215 55 Extension for reply within first month	0 00			
	116 380 216 190 Extension for reply within second month	0 00			
1. BASIC FILING FEE Large Entity Small Entity	117 870 217 435 Extension for reply within third month	0 00			
Fee Fee Fee Fee Description	118 1,360 218 680 Extension for reply within fourth month	0.00			
5045 (V) 5045 (V)	128 1,850 228 925 Extension for reply within fifth month	0.00			
101 690 201 345 Utility filing fee 710.00	119 300 219 150 Notice of Appeal	0.00			
107 480 207 240 Plant filing fee	120 300 220 150 Filing a brief in support of an appeal	0 00			
	121 260 221 130 Request for oral hearing	0 00			
	138 1,510 138 1,510 Petition to institute a public use proceeding	0 00			
	140 110 240 55 Petition to revive - unavoidable	0 00			
SUBTOTAL (1) (\$) 710.00	141 1,210 241 605 Petition to revive - unintentional	0 00			
2. EXTRA CLAIM FEES	142 1,210 242 605 Utility issue fee (or reissue)	0 00			
Fee from Ext <u>ra Claims below</u> Fee Paid		0 00			
Total Claims $\boxed{14}$ -20** $=\boxed{0}$ \times $\boxed{18}$ $=\boxed{0}$	144 580 244 290 Plant issue fee	0 00			
Independent 6 - 3** = 3 × 80 = 240	122 130 122 130 Petitions to the Commissioner	0 00			
Multiple Dependent =0	123 50 123 50 Petitions related to provisional applications	0.00			
**or number previously paid, if greater, For Reissues, see below	126 240 126 240 Submission of Information Disclosure Stmt	0.00			
Large Entity Small Entity Fee Fee Fee Fee Fee Description Code (\$) Code (\$)	581 40 581 40 Recording each patent assignment per property (times number of properties)	0 00			
103 18 203 9 Claims in excess of 20	146 690 246 345 Filing a submission after final rejection (37 CFR § 1 129(a))	0.00			
102 78 202 39 Independent claims in excess of 3	149 690 249 345 For each additional invention to be	0 00			
104 260 204 130 Multiple dependent claim, if not paid	examined (37 CFR § 1 129(b))	0 00			
109 78 209 39 ** Reissue independent claims over original patent	Other fee (specify)	0 00			
110 18 210 9 ** Reissue claims in excess of 20 and over original patent	Other fee (specify)	0.00			
SUBTOTAL (2) (\$) 240.00	·Reduced by Basic Filing Fee Paid SUBTOTAL (3) (\$) 0.0	00			
AUDITED DV	Complete /if applicable)				

Submitted by

Name (Print/Type) Melvin Krausi
Signature

Registration No (Attorney/Agent) 22,466

Registration No (Attorney/Agent) 22,466

Date Nov. 16, 2000

WARNING:

Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

25

5

REPRODUCTION APPARATUS AND REPRODUCTION METHOD OF DIGITAL VIDEO SIGNAL OR AUDIO SIGNAL CROSS REFERENCE TO RELATED APPLICATION

This is a continuation of U.S. application Serial No. 09/290,251, filed April 13, 1999, the subject matter of which is incorporated by reference herein.

BACKGROUND OF THE INVENTION

The present invention relates to a reproduction apparatus for a signal recorded on a medium such as an optical storage medium, and in particular to a technique making it possible to protect a copyright of the signal recorded on the medium.

A digital video disk (DVD) for recording an audio/video (AV) signal compressed by using MPEG2 has a problem that the AV signal could be copied without quality degradation because the AV signal is handled as digital data.

In opposition to this, there has been introduced a technique of an electronic watermark for superimposing information such as permission, inhibition, or permission of only one generation as to copying so that the user may not sense it as described in Nikkei Electronics, February 24, 1997, pp. 99 - 123. In the above described technique, there is described, for example, a method for conducting copying prevention processing on analog output in accordance with a detected signal.

In the case of a medium such as a broadcasting which permits copying only once, however, it is not considered to protect a copyright by restricting reproduction, using a

25

5

10

player of each user, of a pirated edition disk which is produced by copying a signal onto a DVD-R disk (capable of recording the signal once) or the like and thereafter further copying the signal from the DVD-R disk to a DVD-ROM.

SUMMARY OF THE INVENTION

Assuming that copying is permitted only once in broadcasting or the like, an object of the present invention is to provide a technique for preventing a pirated edition disk which is produced by recording a signal onto a DVD-R disk (capable of recording the signal once), a DVD-RAM disk (rewritable), or the like and thereafter illegally copying the recorded signal to a DVD-ROM, from being reproduced by an ordinary user's player capable of reproducing DVD-ROM, DVD-R and DVD-RAM disks.

Another object of the present invention is to report the cause of the reproduction stoppage to the user correctly in the case where reproduction is inhibited.

Originally, a medium allowing copying only once does not exist in DVD-ROM disks. In other words, it is impossible in DVD-ROMs to detect information which has permitted copying of only one generation, from video data. In the case where a signal from a medium permitting copying only once, such as broadcasting, is recorded on a recordable medium such as DVD-R/RAM and the recorded signal is copied onto a DVD-ROM to produce a pirated edition, information which has permitted copying of only one generation is detected from the video data. Therefore, in accordance with an aspect of the present invention, a means for identifying whether a disk is a DVD-R,

25

5

10

a DVD-RAM, or a DVD-ROM, and a means for detecting superimposed or embedded information concerning permission of copying from video data are provided. If the disk is a DVD-ROM and information identifying that copying of one generation has been permitted, such as an electronic watermark and copying protect cryptographic information is detected, then reproduction from the disk is inhibited, the reason of the reproduction stoppage is provided. So, the fact that the reproduction has been stopped due to a copyright problem is reported to the user. As a result, the above described objects are achieved.

BRIEF DESCRIPTION OF THE DRAWING

- FIG. 1 is a block circuit diagram of a DVD reproduction apparatus showing a first embodiment of the present invention;
- FIG. 2 is a block circuit diagram of a DVD reproduction apparatus showing a second embodiment of the present invention;
- FIG. 3 is a block circuit diagram of a DVD reproduction apparatus showing a third embodiment of the present invention; and
- FIG. 4 is a block circuit diagram of a DVD reproduction apparatus showing a fourth embodiment of the present invention.

DESCRIPTION OF THE EMBODIMENTS

- A first embodiment of the present invention will now be described by referring to the drawing.
- FIG. 1 is a block diagram of a DVD reproduction apparatus showing an embodiment of the present invention. Numeral 101

5

10

denotes a DVD-ROM disk, a DVD-R disk, or a DVD-RAM disk having video data or the like recorded thereon. In the present embodiment, video data or audio data having copying permission information superimposed thereon or embedded therein is recorded in each of the above described disks. The superimposed copying permission information cannot be altered without significantly degrading the quality of the original video data or audio data. A disk identification code (a code for identifying whether the disk is a disk dedicated for reproduction) is further added to the video data or audio Numeral 102 denotes an optical pickup for detecting a signal from the disk 101. Numeral 103 denotes a preamplifier for conducting amplification, waveform equalization, and the like on a signal detected by the optical pickup. Numeral 104 denotes a demodulation circuit for converting a reproduced signal to binary values and conducting bit synchronization and demodulation. Numeral 105 denotes a RAM for temporarily storing the reproduced data thus demodulated. Numeral 106 denotes an error correction circuit for conducting error correction processing on data demodulated and stored in the RAM 105. Numeral 107 denotes a detection circuit for detecting a disk identification code recorded on the disk together with the video data or the like. Numeral 108 denotes a detection circuit for detecting superimposed copying permission information from the video data. Numeral 109 denotes a circuit for generating a disk reproduction stopping signal 114 from the detected identification code and the copying permission information. If the disk reproduction

5

10

stopping signal 114 has been generated, then the error correction circuit 106 destroys data instead of correcting data, and simultaneously generates a flag 118 indicating that an error is incorrectable. Numeral 110 denotes a message information generation circuit for generating video data (such as characters or an illustration) or an audio signal indicating that the reproduction is impossible. Numeral 111 denotes a selection circuit for selecting either data subjected to correction processing stored in the RAM 105 or message information supplied from the message information generation circuit, in accordance with the disk reproduction stopping signal 114. Numeral 112 denotes an output control circuit for conducting timing control and the like to output data from the selection circuit 111. Numeral 113 denotes a data output terminal. Numeral 115 denotes an interface for a microcomputer. Numeral 121 denotes a microcontroller for controlling a signal processing device 120 formed of components 104, 105, 106, 107, 108, 109, 110, 111, 112, 114 and 115. Numeral 122 denotes a data/signal transfer bus among the demodulation circuit 104, the RAM 105, the error correction circuit 106, the detection circuits 107 and 108, and the selection circuit 110.

Reproduction from a disk in the present DVD reproduction apparatus will hereafter be described.

A signal recorded on the disk 101 is converted to an electric signal by the pickup 102. The electric signal is subjected in the preamplifier 103 to amplification and waveform equalization. Thereafter, in the demodulation

5

10

circuit 104, the reproduced signal is converted to binary values, and subjected to bit synchronization and demodulation. The reproduced data thus demodulated is temporarily stored in the RAM 105. The stored data is subjected to error correction processing in the error correction circuit 106. The reproduced data thus corrected is sent to the copying permission information detection circuit 108. The copying permission information detection circuit 108 detects the superimposed copying permission information from the reproduced data. The copying permission information indicates which of the following types the recorded data is:

1) copying is possible; 2) copying is inhibited; and 3) copying of only one generation was permitted.

This detected information is sent to the disk reproduction stopping signal generation circuit 109. The disk identification code detection circuit detects the disk identification code added to the video data or audio data, and sends a result to the disk reproduction stopping signal generation circuit 109. The disk identification code identifies 1) a disk dedicated to reproduction, or 2) a recordable disk. If the copying permission information represents "copying of only one generation was permitted" and the disk identification code is judged to be a disk dedicated to reproduction, then the disk reproduction stopping signal generation circuit 109 makes the disk reproduction stopping signal 114 active. Upon the disk reproduction stopping signal 114 becoming active, the error correction circuit 106 destroys the reproduced data stored in the RAM and sends a flag

5

10

indicating that error is incorrectable to the microcontroller 115. Upon the disk reproduction stopping signal 114 becoming active, the message information generation circuit 110 generates video or audio message data indicating that the reproduction has been stopped due to violation of copying consent. The above described message information may include where to make contact with a copyright managing organization (such as its telephone number, address, and the like).

The message information generation circuit 110 may be a ROM or the like storing generated data. Normally, the selection circuit 111 selects reproduced data read out from the RAM. When the disk reproduction stopping signal 114 is active, the selection circuit 111 selects the message information supplied from the message information generation circuit 110.

As heretofore described, in the present embodiment, it is possible to inhibit reproduction of a pirated edition disk which is produced by temporarily recording a video signal or an audio signal from broadcasting which may be permitted to be copied by only one generation onto a DVD-R or DVD-RAM, and then copying the video signal or the audio signal onto a DVD-ROM on the basis of the DVD-R or DVD-RAM.

Furthermore, by outputting the message signal, users can recognize that the reproduction inhibition is not caused by a failure of the reproduction apparatus or a damage of the disk, but caused by a problem of the copyright. In addition, by displaying where to make contact with the copyright managing organization, it is possible to collect information for

25

10

5

identifying a person who produced the pirated edition from Furthermore, in the case of a violation of a copyright, destruction of data is also conducted. In the case where the signal processing device 120 is formed as a single semiconductor chip, therefore, data is destroyed and cannot be read out, even if software of the micro-controller is falsified and correction impossibility flag is disregarded. If the disk reproduction stopping signal 114 in the disk reproduction stopping signal generation circuit 109 is made active, provided that the copying permission information indicates "copying of only one generation was permitted" and the disk identification code is judged to be a disk dedicated to reproduction or provided that the copying permission information is "copying is inhibited" and the disk identification code is judged to a recordable disk, then a DVD-R/RAM produced by illegally recording contents of a disk inhibited from being copied can also be prevented from being reproduced. According to the present embodiment, a reproduction apparatus capable of sufficiently protecting a copyright can be provided.

A second embodiment of the present invention will now be described.

FIG. 2 is a block diagram of a DVD reproduction apparatus showing the second embodiment.

The disk 101 reproduced in the present embodiment is intended for a DVD-ROM, a DVD-R, or a DVD-RAM. Among them, groove-shaped tracks are wobbled in the DVD-RAM/R. Therefore, a push-pull signal for tracking is modulated by the wobble.

25

5

10

This wobble is required to effect tracking at the time of recording, and it does not exist in the disk dedicated to reproduction.

The present embodiment is the same as the first embodiment except the following three points:

- 1) A wobble detection circuit 116 is provided;
- 2) A push-pull signal terminal is provided in the preamplifier 103, and it is connected to the wobble detection circuit 116; and
- that there is no wobbling, or when the disk identification code detection circuit 107 has judged the disk to be a disk dedicated to reproduction and simultaneously therewith the copying permission information detection circuit 108 has judged that copying of only one generation was permitted, the disk reproduction stopping signal generation circuit 109 makes the disk reproduction stopping signal 114 active.

In the present embodiment, at the same time that data is reproduced in the same way as the first embodiment, wobble detection is conducted by the wobble detection circuit 116.

When either the wobble detection circuit 116 or the disk identification code detection circuit 107 has judged the disk to be a disk dedicated to reproduction and simultaneously therewith the copying permission information detection circuit 108 has judged that copying of only one generation was permitted, the disk reproduction stopping signal generation circuit 109 makes the disk reproduction stopping signal 114 active. Even if the disk identification code is rewritten,

25

5

10

therefore, reproduction is inhibited certainly.

As heretofore described, in the present embodiment, it is possible to inhibit reproduction of a pirated edition disk which is produced by temporarily recording a video signal or an audio signal from broadcasting which may be permitted to be copied by only one generation onto a DVD-R or DVD-RAM, and then copying the video signal or the audio signal onto a In the present DVD-ROM on the basis of the DVD-R or DVD-RAM. embodiment, detection of a pirated edition is conducted certainly by judging the disk to be a disk dedicated to reproduction provided that there is no wobble or provided that the identification code indicates a disk dedicated to reproduction. Even if the condition that the identification code indicates a disk dedicated to reproduction is removed from the decision conditions, however, the same effects as the those of the first embodiment are obtained.

A third embodiment of the present invention will now be described by referring to drawing.

FIG. 3 is a block diagram of a DVD reproduction apparatus showing the third embodiment.

The present embodiment is the same as the first embodiment except the following three points:

- A reflectance identification circuit 117 for processing reflectance information of a disk derived by the preamplifier 103 is provided;
- 2) A terminal for outputting information of the reflectance is provided in the preamplifier 103, and the terminal is connected to the reflectance identification

10

tion, then the party men even as the party of the party o

20

25

circuit 117; and

3) When the reflectance identification circuit 117, the wobble detection circuit 116, or the disk identification code detection circuit 107 has judged the disk to be a disk dedicated to reproduction and simultaneously therewith the copying permission information detection circuit 108 has judged that copying of only one generation was permitted, the disk reproduction stopping signal generation circuit 109 makes the disk reproduction stopping signal 114 active.

At the same time that data is reproduced in the same way as the second embodiment, reflectance information is sent from the preamplifier 103 to the reflectance identifying circuit 117 in the present embodiment. The reflectance identifying circuit 117 has a threshold value for the reflectance and identifies a disk yielding a reflectance value which is equal to or larger than the threshold value, as a disk dedicated to reproduction.

When the reflectance identifying circuit 117, the wobble detection circuit 116, or the disk identification code detection circuit 107 has judged the disk to be a disk dedicated to reproduction and simultaneously therewith the copying permission information detection circuit 108 has judged that copying of only one generation was permitted, the disk reproduction stopping signal generation circuit 109 makes the disk reproduction stopping signal 114 active.

Even if the disk identification code is rewritten, reproduction is inhibited certainly. In the present embodiment, detection of a pirated edition is conducted

10

certainly by judging the disk to be a disk dedicated to reproduction provided that the reflectance is equal to or larger than the threshold value, provided that there is no wobble, or provided that the identification code indicates a disk dedicated to reproduction. Even if the disk is judged to be a disk dedicated to reproduction provided that some combination of the three conditions is satisfied, however, the same effects as the those of the first embodiment are obtained.

A fourth embodiment of the present invention will now be described by referring to drawing.

FIG. 4 is a block diagram of a DVD reproduction apparatus showing the fourth embodiment.

Instead of inputting the output of the message information generation circuit 110 to the selection circuit 111 and inputting the output of the selection circuit 111 to the output control circuit 112, the output of the message information generation circuit 110 is written into the RAM 105 via a RAM write controller 119. Components other than them are common to the third embodiment. In the case where the disk reproduction stopping signal 114 has become active, overwriting is conducted on video data or audio data which should be originally outputted in the present embodiment. As a result, there are obtained the same effects as those of the case where the output of the message information generation circuit 110 is inputted to the selection circuit 111 and the output of the selection circuit Ill is inputted to the output control circuit 112 as in the second embodiment.

. 25

5

10

Furthermore, in the first to fourth embodiments, the message information for the user is generated in the reproduction apparatus. However, the same effects are also obtained by providing a terminal for outputting the disk reproduction stopping signal 114, sending the disk reproduction stopping signal 114 to a video data display apparatus, an audio output apparatus, a compressed video data or audio data decompression apparatus, or the like, and causing the apparatus receiving the disk reproduction stopping signal 114 to generate the message information.

As heretofore described, reproduction is inhibited according to the present invention in the case where the copying permission information superimposed on the video signal or embedded therein indicates that copying of only one generation was permitted and the disk is judged to be a DVD-ROM. As a result, it is possible to inhibit reproduction from a disk which is produced by temporarily recording video or audio data permitted as to copy of one generation onto a DVD-R/RAM and thereafter illegally copying the recorded data to a DVD-ROM. In addition, in the case where reproduction is inhibited, the cause of the reproduction stoppage can be reported to the user correctly.

Throughout these embodiments, function operation of the circuit for detecting the copying permission information and the disk type, the reproduction stopping signal generation circuit, and the like can be effected by execution of them in a processor in a program form. Therefore, at least a part of the circuit configuration can be implemented in a software

fashion by execution, in the processor, of a program stored in memories.

20

25

10

5

WHAT IS CLAIMED IS:

1. A reproduction apparatus for reproducing video data and/or audio data from a medium dedicated to reproduction and/or a recordable medium having video data and/or audio data recorded thereon, said video data and/or audio data being generated by superimposing information concerning copying consent on a digitized video signal or audio signal which has undergone addition of an error correction code for error correction and then modulated in accordance with a modulation rule adapted for the recording medium, said reproduction apparatus comprising:

demodulating means for demodulating data modulated in accordance with said modulation rule;

temporal store means for holding the data demodulated by said demodulating means;

error-correcting means for error-correcting the demodulated data stored in said temporal store means based on the error correction code, the error-corrected data being stored in said temporal store means;

reproducing means for reproducing the superimposed information concerning copying consent from the error-corrected demodulated data processed by said error-correcting means and stored in said temporal store means; and

output control means for performing output control of the reproduced data based on said reproduced information concerning copying consent stored in the temporal store means.

; :

10

25

20

- 2. A reproduction apparatus for reproducing video data and/or audio data according to claim 1, wherein said temporal store means is a RAM.
- 3. A reproduction apparatus for reproducing video data and/or audio data according to claim 2, wherein said demodulating means, said error-correcting means and said copying consent information reproduction means are connected to said RAM, respectively.
- 4. A reproduction apparatus for reproducing video data and/or audio data according to claim 3, wherein said RAM is constituted by a single RAM.
- 5. A reproduction apparatus for reproducing video data and/or audio data according to claim 2, wherein said copying consent information reproducing means, said demodulating means, said error-correcting means and said RAM are integrated in a single semiconductor device.
- 6. A reproduction apparatus for reproducing video data and/or audio data from a medium dedicated to reproduction and/or a recordable medium having video data and/or audio data recorded thereon, said data and/or audio data being generated by superimposing information concerning copying consent on a digitized video signal or audio signal which has undergone addition of an error correction code for error correction and then modulated in accordance with a modulation rule adapted

25

;

5

10

for the recording medium, said reproduction apparatus comprising:

demodulating means for demodulating data modulated in accordance with said modulation rule;

a temporal store means for holding the data demodulated by said demodulating means;

error-correcting means for error-correcting the demodulated data stored in said temporal store means based on an error correction code, the error-corrected data being stored in said temporal store means;

reproducing means for reproducing the superimposed information concerning copying consent from the error-corrected video data and/or audio data processed by said error-correcting means and stored in said temporal store means; and

means for stopping reproduction of the error-corrected video data and/or audio data in accordance with the information concerning copying consent from said copying consent information reproducing means;

wherein said demodulating means, said temporal store means, said error-correcting means, said copying consent information reproducing means and said reproduction stopping means are integrated in a single semiconductor device.

7. A reproduction apparatus for reproducing video data and/or audio data from a medium dedicated to reproduction and/or a recordable medium having video data and/or audio data recorded thereon, said video data and/or audio data being

25

10

5

\$

generated by superimposing information concerning copying consent on a digitized video signal or audio signal which has undergone addition of an error correction code for error correction and then modulated in accordance with a modulation rule adapted for the recording medium, said reproduction apparatus comprising:

a demodulator which demodulates data modulated in accordance with said modulation rule;

a temporal store which holds the data demodulated by said demodulator;

an error-corrector which for error-corrects the demodulated data stored in said temporal store based on the error correction code, the error-corrected data being stored in said temporal store;

a reproducer which for reproduces the superimposed information concerning copying consent from the error-corrected demodulated data processed by said error-corrector and stored in said temporal store; and

an output controller which performs output control of the reproduced data based on said reproduced information concerning copying consent stored in the temporal store.

- 8. A reproduction apparatus for reproducing video data and/or audio data according to claim 7, wherein said temporal store is a RAM.
- 9. A reproduction apparatus for reproducing video data and/or audio data according to claim 8, wherein said

demodulator, said error-corrector and said copying consent information reproducer are connected to said RAM, respectively.

5

10

20

25

- 10. A reproduction apparatus for reproducing video data and/or audio data according to claim 9, wherein said RAM is constituted by a single RAM.
- 11. A reproduction apparatus for reproducing video data and/or audio data according to claim 2, wherein said copying consent information reproducer, said demodulator, said error-corrector and said RAM are integrated in a single semiconductor device.
- and/or audio data from a medium dedicated to reproduction and/or a recordable medium having video data and/or audio data recorded thereon, said data and/or audio data being generated by superimposing information concerning copying consent on a digitized video signal or audio signal which has undergone addition of an error correction code for error correction and then modulated in accordance with a modulation rule adapted for the recording medium, said reproduction apparatus comprising:
- a demodulator which demodulates data modulated in accordance with said modulation rule;
- a temporal store which holds the data demodulated by said demodulator;

5

10

an error-corrector which error-corrects the demodulated data stored in said temporal store based on an error correction code, the error-corrected data being stored in said temporal store;

a reproducer which reproduces the superimposed information concerning copying consent from the error-corrected video data and/or audio data processed by said error-corrector and stored in said temporal store; and

a reproduction stopper which stops reproduction of the error-corrected video data and/or audio data in accordance with the information concerning copying consent from said copying consent information reproducer;

wherein said demodulator, said temporal store, said error-corrector, said copying consent information reproducer and said reproduction stopper are integrated in a single semiconductor device.

13. A method for reproducing from a medium dedicated to reproduction and/or a recordable medium having video data and/or audio data recorded thereon, said data and/or audio data being generated by superimposing information concerning copying consent on a digitized video signal or audio signal which has being undergone addition of an error correction code for error correction and then modulated in accordance with a modulation rule adapted for the recording medium, in a reproduction apparatus comprising a demodulator which demodulates in accordance with said modulation rule; a temporal store which holds the data demodulated by said

10

5

demodulator; an error-corrector which for error-corrects the demodulated data stored in said temporal store based on the error correction code; a reproducer which for reproduces the superimposed information concerning copying consent from said video data and/or audio data; and an output controller which controls an output of the apparatus, said method comprising the steps:

demodulating modulated data by said demodulator;

temporarily storing the demodulated data in said temporal store;

error-correcting the demodulated data stored in said temporal store means by said error-corrector to provide error-corrected demodulated data;

reproducing the superimposed information concerning copying consent from said error-corrected demodulated data stored in said temporal store by said copying consent information reproducer; and

performing output control of the apparatus by said output controller in accordance with the information concerning copying consent reproduced by said copying consent information reproducer.

14. A method for reproducing from a medium dedicated to reproduction and/or a recordable medium having video data and/or audio data recorded thereon, said data and/or audio data being generated by superimposing information concerning copying consent on a digitized video signal or audio signal which has being undergone addition of an error correction code

25

10

5

for error correction and then modulated in accordance with a modulation rule adapted for the recording medium, in a reproduction apparatus comprising demodulating means for demodulating in accordance with said modulation rule; a temporal store means for holding the data demodulated by said demodulating means; error-correcting means for error-correcting the demodulated data stored in said temporal store means based on the error correction code; reproducing means for reproducing the superimposed information concerning copying consent from said video data and/or audio data; and output control means for controlling an output of the apparatus, said method comprising the steps:

demodulating modulated data by said demodulation means; temporarily storing the demodulated data in said temporal store mean;

error-correcting the demodulated data stored in said temporal store means by said error-correcting means to provide error-corrected demodulated data;

reproducing the superimposed information concerning copying consent from said error-corrected demodulated data stored in said temporal store means by said copying consent information reproducing means; and


performing output control of the apparatus by said output control means in accordance with the information concerning copying consent reproduced by said copying consent information reproducing means.


5


10


ABSTRACT OF THE DISCLOSURE

A reproduction apparatus and method for reproducing video data and/or audio data from a medium dedicated to reproduction and/or a recordable medium having video data and/or audio data recorded thereon. The video data and/or audio data is generated by superimposing information concerning copying consent on a digitized video signal or audio signal which has undergone addition of an error correction code for error correction and then modulated in accordance with a modulation rule adapted for the recording medium. The reproduction apparatus includes a demodulator for demodulating data modulated in accordance with the modulation rule, a temporal store for holding the data demodulated by the demodulator, an error-corrector for error-correcting the demodulated data stored in the temporal store, based on an error correction code with the error-corrected data being stored in the temporal store. A reproducer reproduces the superimposed information concerning copying consent from the errorcorrected demodulated data processed by the error-corrector and stored in the temporal store and an output controller performs output control of the reproduced data based on the reproduced information concerning copying consent stored in the temporal store.









E4570-01 Copy (*)

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name, I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: "REPRODUCTION APPARATUS AND REPRODUCTION METHOD OF DIGITAL VIDEO SIGNAL OR AUDIO SIGNAL" X is attached hereto. the specification of which (check one) was filed on . as Application Serial No. _____ and was amended on (if applicable) I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information which is material to the examination of this application in accordance +E with Title 37, Code of Federal Regulations, \$1.56(a). I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed: Priority Claimed Prior Foreign Application(s) 3: 14 April, 1998 Japan 10-102385 (Day/Month/Year Filed) (Country) (Number) (Day/Month/Year Filed) (Country) (Number) (Day/Month/Year Filed) (Country) (Number) (Day/Month/Year Filed) (Number) (Country) (Day/Month/Year Filed) (Number) (Country) (Country) (Number) I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, \$1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application: (Status: patented, pending, abandoned) (Filing Date) (Application Serial No.) (Filing Date) (Status: patented, pending, abandoned) (Application Serial No.) (Status: patented, pending, abandoned) (Filing Date) (Application Serial No.)

(Filing Date)

(Application Serial No.)

(Status: patented, pending, abandoned)

E4570-01

I hereby appoint as principal attorneys; Donald R. Antonelli, Reg. No. 20,296; David T. Terry, Reg. No. 20,178; Melvin Kraus, Reg. No. 22,466; Stanley A. Wal, Reg. No. 26,432; William I. Solomon, Reg. No. 23,565; Gregory E. Montone, Reg. No. 28,141; Ronald J. Shore, Reg. No. 28,577; Donald E. Stout, Reg. No. 26,422; Alan E. Schiavelli, Reg. No. 32,087; James N. Dresser, Reg. No. 22,973 and Carl I. Brundidge, Reg. No. 29,621 to prosecute and transact all business connected with this application and any related United States application and international applications. Please direct all communications to the following address:

Antonelli, Terry, Stout & Kraus Suite 1800 1300 North Seventeenth Street Arlington, Virginia 22209 Telephone: (703) 312-6600 Fax: (703) 312-6666.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further, that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United State Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

					(Full Name)		(Signature)
Date	Apr	il 1,	1999	Inventor	Yutaka NAGAI		Mataka hagai
Residen			ohama-shi	, Japan	ado-3-chome, Tot	Citizenship _	Japan
Bost O	Affice	Address	: Japan	_			
Tota	Apr	il 1,	1999	Inventor	Toshifumi TAKEU	JCHI <	Cochitam) Catsono
		Toky	yo, Japan			Citizenship _	Japan
Post O	ffice	Address	11-9-	104, Nis	hikamata-4-chome	e, Ota-ku	, Tokyo, Japan.
Date				Inventor	-		
Residen	nce					Citizenship _	
770.2							
* Amos							•
£							
Date				Inventor			
Resider	ace					Citizenship _	
Post O	ffice	Address	·		· · · · · · · · · · · · · · · · · · ·		
Residen	ace	<u> </u>				Citizenship _	
Post O	ffice	Address					
Date				Inventor			
Residen	nce					Citizenship _	
Post O	ffice	Address					
Date				Inventor			
Residen	nce					Citizenship _	
Post O	ffice	Address					
Residen	nce					Citizenship _	
Post O	ffice	Address					
Residen	nce					Citizenship _	
Post O	ffice	Address	·				